



Palets  
Pla d'Urgell s.l.  
donem més vida a la fusta



[www.paletspladurgell.cat](http://www.paletspladurgell.cat)



973 580 475



[info@paletspladurgell.cat](mailto:info@paletspladurgell.cat)



# EKO-KWU



Palets Pla d'Urgell. Crta. de Bellpuig s/n,  
25260 Ivars d'Urgell - Lleida

Manufactured  
by:

**ELEKTROMET**<sup>®</sup>

ELEKTROMET reserves the  
right to make technical  
changes



# EKO-KWU

Parameters		Units	EKO KWU 14	EKO KWU 18	EKO KWU 23	EKO KWU 28	EKO KWU 33
Catalogue number		KW	414-14-100	414-18-100	414-23-100	414-28-100	414-33-100
Nominal power		KW	14	18	23	28	33
Minimal power		%	4	6	8	9	10
Efficiency		%	aprox. 80				
Min/max temperature		°C	40/85				
Maximum working pressure of the boiler		MPa	0,25				
Capacity of the fuel container		kg	22	30	38	48	76
Water capacity		dm <sup>3</sup>	60	66	77	89	106
Required chimney draught		Pa	20 ~ 35				
Chimney section		cm <sup>3</sup>	aprox. 350				
Diameter of chimney connector		mm	160	160	160	160	160
Dimensions	height	mm	1260	1320	1360	1410	1510
	width	mm	450	490	490	510	550
	depth	mm	765	765	845	900	945
<b>Boiler's connections</b>	Heating water (outlet)		1 x 1 ½", 2 x 1"				
	Heating water (return)		1 x 1 ½"				
Drain			½"				
Voltage		V	1 ~ 230 V / 50 Hz TN-5				
Installed capacity		W	80				
Boiler's weight without water		kg	190	220	240	280	310

\* **Fuel:** Briquettes, seasoned wood and coal.

\* **Option of opening the door on the right and left of the boiler. It is required to determine before ordering.**

