



Palets  
Pla d'Urgell s.l.  
donem més vida a la fusta



[www.paletspladurgell.cat](http://www.paletspladurgell.cat)



973 580 475



[info@paletspladurgell.cat](mailto:info@paletspladurgell.cat)



# EKO-KWP "MULTI"



Palets Pla d'Urgell. Crta. de Bellpuig s/n,  
25260 Ivars d'Urgell - Lleida

Manufactured  
by:

**ELEKTROMET**®

ELEKTROMET reserves the  
right to make technical  
changes



# EKO-KWP "MULTI"

Parameters		Units	EKO KWP 25
Catalogue number			460-25-101 P / 460-25-101 L
Nominal power		kW	25
Efficiency		%	90
Boiler's heating surface		m <sup>2</sup>	2,6
Water capacity		dm <sup>3</sup>	108
Maximum working pressure in the boiler		bar	2,5
Range of control power		°C	55-90
Recommended temperature of heating water		°C	65
Diameter of chimney connector		mm	160
Required chimney draught		Pa	10-20
Boiler's weight without water		kg	420
<b>Boiler's connections</b>	Heating water (outlet)		3 x 1 ½"
	Heating water (return)		1 x 1 ½"

\* **Fuel:** pellets with diameter 6-8mm on the properties in accordance with EN plus A1.

\* **Possibility to add an emergency cast iron grate to burn wood or briquettes.**

\* **Option to place the feeding tank on the right and left of the boiler. It is required to determine before ordering.**

